

# Venhart 600AA Acrylic Tape



## PRODUCT DESCRIPTION

Venhart 600AA is a biaxially oriented polypropylene tape with quick release acrylic solvent adhesive. It has good adhesion, initial viscosity, and retention, high tensile strength, light weight, is non-toxic. Medium tack that can be used in a wide variety of general packaging and sealing purposes.



## APPLICATION INFORMATION

- Used to seal boxes, packaging, and other containers for storage and shipping.
- Can be applied to plastic, paper, and cardboard.
- Performs well in low temperatures making it ideal for cold rooms and freezers.
- Used in tape guns and auto carton sealers.



## PHYSICAL PROPERTIES

|                         |            |                          |                 |
|-------------------------|------------|--------------------------|-----------------|
| <b>Total Thickness</b>  | 55µm       | <b>Adhesive Type</b>     | Solvent Acrylic |
| <b>Film Thickness</b>   | 32µm       | <b>Elongation</b>        | 100%            |
| <b>Tensile Strength</b> | 95N / 25mm | <b>Adhesion to Steel</b> | 6N / 25mm       |



## AVAILABLE SIZES & COLOURS

\* Tolerances: Thickness +/- 2µm; Width +/- 1mm

| CODE     | SIZE         | ROLLS / CARTON | Colour       |
|----------|--------------|----------------|--------------|
| A2427524 | 24mm x 75m   | 72             | Brown, Clear |
| A2427536 | 36mm x 75m   | 48             |              |
| A2427548 | 48mm x 75m   | 36             |              |
| A24-7572 | 72mm x 75m   | 24             |              |
| A24-9936 | 36mm x 1000m | 8              |              |
| A24-9948 | 48mm x 1000m | 6              |              |



## STORAGE & TEMPERATURE CONDITIONS

|                         |                                                                                                                                                        |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Storage</b>          | Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. |
| <b>Storage Temp</b>     | -10°C – 60°C                                                                                                                                           |
| <b>Application Temp</b> | 10°C – 40°C                                                                                                                                            |

Note: The following technical information and data should be considered representative or typical only.